## Product data sheet Characteristics

## 9700A

# Magnetic flow tube-demanding applications including corrosive, abrasive media

Life Is On F





#### Main

Range of product	Flow
Product or component type	Magnetic flowmeter transmitter
Device application	To measure the flow of pressure for liquid, gas, steam
Market segment	Pharmaceutical Chemical Paper and pulp

#### Complementary

Product specific application	To measure flow with low conductivity media To measure flow with high solid media To measure flow with entrained air To measure flow with inhomogeneous media To measure flow with abrasive media To measure flow with corrosive media Mining minerals and metals Oil and gas
Measurement accuracy	+/- 0.3 % of reading with IMT31A +/- 0.2 % of reading with IMT33A +/- 0.5 % of reading with IMT30A
Drift of the sensitivity	+/- 0.01 %
Mounting location	Wall mounting (with IMT30A) Wall mounting (with IMT31A) Field mounting (with IMT33A)
Device composition	Liner in PFA (perfluoroalkoxy) Liner in PTFE (polytetrafluoroethylene) Liner in ETFE (ethylene tetrafluoroethylene) Liner in polyurethane Electrode in hastelloy Electrode in stainless steel Electrode in titanium Electrode in tantalum electrode in platinium
Tube diameter	101200 Mm 102000 Mm 9.651219.20 Mm 9.652032.00 Mm
Name of test	Vibration Shocks
Mounting support	Flange conforming to EN 1092-1 Flange conforming to ASME B16.5 Flange conforming to JIS

#### Environment

Ambient air temperature for operation	-40180 °C with PFA or PTFE liner for remote	
·	-40140 °C with PFA or PTFE liner for IMT33A	
	-40120 °C with PFA or PTFE liner for IMT30A	
	-40120 °C with PFA or PTFE liner for IMT31A	
	-580 °C with hard rubber liner	
	-560 °C with soft rubber liner	
	-565 °C with polyurethane liner	
Product certifications	CE	
	ATEX	
	FM	
	CSA	
	IECEx	
	NEPSI	
Standards	IEC 60529	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherence in not to be used for determining suitability or reliability of these products for specific user applications. It is the douty of any sub user or integrator to perform the appropriate and complete risk analysis, evaluating of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and- lead compounds, which is known to the State of California to cause can- cer and birth defects or other reproductive harm. For more information go- to www.P65Warnings.ca.gov

Product Life Status : Commercialised